

JALAS® 1378 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI

ASTM F2413 -18
M/I/C
SD 35 PR

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, extremely warm, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Heavy Duty

PLATFORM Arctic Grip

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1.6-1.8

PRONOSE-MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester fur, Thinsulate™

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Winter

INSOLE MATERIAL Textile, aluminium foil, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces, Zipper

COLOUR Black, Blue



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1378-35	6408487506222	47	1378-47	6408487506345
36	1378-36	6408487506239	48	1378-48	6408487506352
37	1378-37	6408487506246			
38	1378-38	6408487506253			
39	1378-39	6408487506260			
40	1378-40	6408487506277			
41	1378-41	6408487506284			
42	1378-42	6408487506291			
43	1378-43	6408487506307			
44	1378-44	6408487506314			
45	1378-45	6408487506321			
46	1378-46	6408487506338			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1378 HEAVY DUTY

FEATURES

ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, extra shoelaces, pull loops, snow lock, zipper, antistatic, water repellent, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, contact with cold, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, slippery environments, cold environments, harsh environments

2(3)



Composite toecap



Zipper



Nail protection in steel



Winter model



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 1378 HEAVY DUTY



COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE



Composite toecap



Zipper



Nail protection in steel



Winter model



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.